

6 Sheffield Street Paraparaumu 5032 Ph: 04 296 1089 Fax: 04 298 0059

**Product: Oilpro SS 10W-40** 

#### 1. Product Identification

**Product Details** 

Product Identifier Oilpro SS 10W-40
Product Code OPSS1040
Recommended Use Engine Oil

**Manufacturer or Supplier Details** 

Supplier Pennzcorp

Address 6 Sheffield Street, Paraparaumu, 5032 Telephone +64 4 296 1089 (Business Hours)

Fax +64 4 298 0059

Emergency Telephone Number 04 296 1089

Email sales@Pennz-corp.co.nz

### 2. Hazard(s) Identification

#### **GHS Classification**

Not classified as hazardous under the Globally Harmonised System (GHS)

#### **GHS Label Elements**

Hazard Pictogram No hazard symbol required

Signal Word No signal word

**Hazard Statements** 

Physical Hazards Not classified as a physical hazard under GHS criteria
Health Hazards Not classified as a health hazard under GHS criteria

Environmental Hazards Not classified as an environmental hazard under GHS criteria

**Precautionary Statements** 

Prevention Not applicable
Response Not applicable
Storage Not applicable
Disposal Not applicable
Supplemental label elements Not applicable

Other hazards which do not Prolonged or repeated skin contact without proper cleaning can clog the pores of

result in classification the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain

harmful impurities.



6 Sheffield Street Paraparaumu 5032

Pennzcorp

Ph: 04 296 1089 Fax: 04 298 0059

**Product: Oilpro SS 10W-40** 

### 3. Composition / Information on Ingredients

Chemical Nature: Highly refined mineral oils and proprietary performance additives.

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346

Ingredients:

Ingredient	% (w/w)	CAS Number
Base oil - unspecified	>75 - <95	Varies – See Abbreviations Section 16
Additives – not hazardous	>5 - <25	Not applicable

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First Aid Measures

Eye contact: Flush eye with copious quantities of water.

> If persistent irritation occurs, obtain medical attention. No treatment necessary under normal conditions of use.

Inhalation:

If symptoms persist, obtain medical attention.

Skin contact: Remove contaminated clothing. Flush exposed area with water and follow by

washing with soap if available.

If persistent irritation occurs, obtain medical attention.

If swallowed: In general no treatment is necessary unless large quantities are swallowed. Do not

induce vomiting and obtain medical advice.

Most important symptoms and

effects, both acute and delayed:

Oil acne/folliculitis signs and symptoms may include formation of black pustules

and spots on the skin of exposed areas.

Swallowing may result in nausea, vomiting and/or diarrhoea.

**Protection of first-aiders:** When administering first aid, ensure that you are wearing the appropriate personal

protective equipment according to the incident, injury and surroundings.

Notes to physician: Treat symptomatically.

#### Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

Issue Date: 3 September 2019 Issued by: Pennzcorp Page 2 of 7



6 Sheffield Street Paraparaumu 5032

Pennzcorp

Ph: 04 296 1089 Fax: 04 298 0059

**Product: Oilpro SS 10W-40** 

#### 5. Fire Fighting Measures

Suitable extinguishing equipment:

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may

be used for small fires only.

Unsuitable extinguishing

equipment:

Do not use water in a jet.

Specific hazards during

firefighting:

Combustible liquid. In a fire, or if heated, a pressure increase will occur and the

container may burst with the risk of a subsequent explosion.

May produce toxic fumes if burning including possibly carbon monoxide, airborne solid and liquid particulates and gases and unidentified organic and

inorganic compounds.

Special protective equipment and precautions for firefighters:

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Positive pressure Self-Contained Breathing Apparatus and full turn out

gear should be worn.

HazChem Code: None

#### 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: **Environmental precautions:** 

Avoid contact with skin and eyes, use appropriate personal protective equipment.

Evacuate surrounding areas if necessary. Remove all ignition sources.

Stop leak if without risk. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by

using sand, earth or other appropriate barriers.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Slippery when spilt. Avoid accidents, clean up immediately.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other suitable material and

dispose of properly.

### 7. Handling and Storage

Precautions for safe handling: Use in a well ventilated area.

Wear appropriate protective equipment (See Section 8) and clothing to avoid

inhalation of fumes or mist and contact with skin and eyes.

Containers not in use should be closed.

Do not smoke.

Always wash hands after handling and prior to eating, drinking, smoking or using

the toilet.

Conditions for safe storage, including any incompatibilities: Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purposes of storage and

handling.

Store in a cool, well ventilated area away from heat and other sources of ignition,

oxidising agents, foodstuffs, and out of direct sunlight. Keep containers securely sealed and protect against damage.





6 Sheffield Street Paraparaumu 5032

Ph: 04 296 1089 Fax: 04 298 0059

# SAFETY DATA SHEET

**Product: Oilpro SS 10W-40** 

### 8. Exposure Control / Personal Protection

No exposure standard has been established, however, the TWA National **National Exposure Standards:** 

> Occupational Health and Safety Commission (NOHSC) exposure standard for oil mist is 5 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible level.

**Biological limit values:** Not available

**Engineering Controls:** Ventilation - Use in well ventilated areas. Where ventilation is inadequate, a local

exhaust ventilation system is required.

**Personal Protective Equipment** 

**Respiratory Protection:** Normally not required, however if mists or vapours are generated in a poorly

ventilated area an approved respirator with a replaceable vapour/mist filter is

recommended.

**Eye Protection:** Safety glasses with side shields, goggles or full face mask as appropriate. Individual

circumstances will dictate the final choice of protection.

Skin / Body Protection: Always wear long sleeves and long trousers or coveralls, and enclosed footwear or

safety boots when handling this product. It is recommended that chemical resistant

gloves (e.g. PVC) be worn when handling this product.

### 9. Physical and Chemical Properties

Appearance amber

**Melting Point** Not available **Boiling Point** Not available Vapour Pressure Not available Solubility in Water Insoluble pH Value Not applicable

Viscosity @ 40°C 98 Viscosity @ 100°C 14 **Specific Gravity** 0.871 Flash Point >210

**Flammability** Combustible Liquid **Auto Ignition** Not available

Temperature

Flammable Limits Not available

#### 10. Stability and Reactivity

Reactivity: No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability: Stable under normal conditions of storage and handling.

Possibility of hazardous

reactions:

Reacts with strong oxidising agents.

Conditions to avoid: Heat, direct sunlight, open flames or other sources of ignition.

**Incompatible Materials:** Strong oxidizing agents.





6 Sheffield Street Paraparaumu 5032 Ph: 04 296 1089 Fax: 04 298 0059

# SAFETY DATA SHEET

**Product: Oilpro SS 10W-40** 

**Hazardous Decomposition** 

**Products:** 

Under normal conditions of storage and use hazardous decomposition products are not expected to be produced.

### 11. Toxicological Information

Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for the individual component(s). Skin and eye contact are the primary routes of exposure although exposure may occur following accidental swallowing.

Acute oral toxicity: LD50 rat: >5,000 mg/kg. Expected to be of low toxicity. Acute toxicity

Acute inhalation toxicity: Not considered to be an inhalation hazard under normal

conditions of use.

Acute dermal toxicity: LD50 rabbit: >5,000 mg/kg. Expected to be of low toxicity.

Skin corrosion/irritation Expected to be slightly irritating. Prolonged or repeated skin contact without proper

cleaning can clog the pores of the skin resulting in disorders such as oil

acne/folliculitis.

Serious eye damage/eye

irritation

Expected to be slightly irritating

Respiratory or skin

sensitization

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Carcinogenicity

Not considered a mutagenic hazard. Not expected to be carcinogenic.

Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies. Highly refined mineral oils are not classified as carcinogenic by the

International Agency for Research on Cancer (IARC).

Reproductive toxicity Not expected to impair fertility. Not expected to be developmental toxicant.

STOT - single exposure Not expected to be a hazard. Not expected to be a hazard. STOT - repeated exposure

**Aspiration toxicity** Not considered an aspiration hazard.

**Further information** USED oils may contain harmful impurities that have accumulated during use.

The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with

caution and skin contact avoided as far as possible.

#### 12. Ecological Information

Eco toxicological data has not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### **Ecotoxicity**

Toxicity to fish (Acute toxicity) Expected to be practically non-toxic. Toxicity to crustacean (Acute toxicity) Expected to be practically non-toxic. Toxicity to algae/aquatic plants (Acute Expected to be practically non-toxic.

toxicity)

Data not available. Toxicity to fish (Chronic toxicity) Data not available. Toxicity to crustacean (Chronic toxicity) Toxicity to microorganisms (Acute toxicity) Data not available.

Issue Date: 3 September 2019 Issued by: Pennzcorp Page 5 of 7



## 6 Sheffield Street

6 Sheffield Street
Paraparaumu 5032

Pennzcorp

Ph: 04 296 1089 Fax: 04 298 0059

# SAFETY DATA SHEET

**Product: Oilpro SS 10W-40** 

Persistence and degradability

Biodegradability Expected to be not readily biodegradable. Major constituents are expected

to be inherently biodegradable, but contains components that may persist

in the environment.

**Bioaccumulative potential** 

Bioaccumulation Contains components with the potential to bio accumulate.

Partition coefficient: n-

octanol/water

Pow: >6 based on information on similar products.

Mobility in soil

Mobility Liquid under most environmental conditions. If it enters soil, it will adsorb

to soil particles and will not be mobile.

Floats on water.

Other adverse effects

Additional ecological information Product is a mixture of non-volatile components which are not expected to

be released to air in any significant quantities.

Not expected to have ozone depletion potential, photochemical ozone

creation potential or global warming potential.

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Mineral oil is not expected to cause any chronic effects to aquatic

organisms at concentrations less than 1 mg/l.

13. Disposal Considerations

**Disposal methods** 

Waste from residues Waste product should not be allowed to contaminate soil or ground water or

be disposed of into the environment.

Disposal should be in accordance with applicable regional, national and local

laws and regulations.

Contaminated packaging Dispose in accordance with prevailing regulations, preferably to a recognised

collector or contractor. The competence of the collector or contractor should

be established beforehand.

Special precautions for landfill or

incineration

No additional special precautions identified.

14. Transport Information

**National Regulations** 

ADG

Not regulated as a dangerous good.

International Regulations

IATA-DGR Not regulated as a dangerous good. IMDG-DGR Not regulated as a dangerous good.

Issue Date: 3 September 2019 Issued by: Pennzcorp Page 6 of 7



**Pennzcorp** 6 Sheffield Street Paraparaumu 5032

Ph: 04 296 1089 Fax: 04 298 0059

**Product: Oilpro SS 10W-40** 

#### 15. Regulatory Information

**Standard Uniform Schedule of Medicine and Poisons** 

Not scheduled

Model Work Health and Safety Regulations - Scheduled Substances

Not listed

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code)

Not regulated

#### 16. Other information

Date of Issue Wednesday, December 21, 2016

**Abbreviations** ADG = Australian Dangerous Goods

GHS = Globally Harmonised System of Classification and Labelling of chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk container

IMDG = International Maritime Dangerous Goods

STEL = Short term exposure limit TWA = time weighted average

Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7,

72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 90669-74-2

#### Other Information

The information contained in this SDS is as accurate as we can ascertain at this time. However, as the information is gleaned from a number of third party sources, Pennzcorp can make no warranty, guarantee or statement as to the reliability or completeness of the information. Pennzcorp will not accept liability of any damages whatsoever arising from the reliance of this information. It is the responsibility of the person handling the product to satisfy themselves as to the suitability and completeness of such information for their own use.

...END OF SDS...